



● Branches

DAIKIN AIRCONDITIONING INDIA PVT. LTD.

12th Floor, Building No. 9, Tower A, DLF Cyber City, DLF Phase III, Gurgaon - 122 002, Haryana, India.
Tel.: 0124-4555444, Fax: 0124-4555333

 **CUSTOMER SUPPORT AT:**
1860-102-9322
serviceref@daikinindia.com

SALES & SERVICE OFFICES

Ahmedabad : Tel: 079-26583013/14	Kolkata : Tel: 033-4060 8019/40659544
Bengaluru : Tel: 080-25590452/54	Lucknow : Tel: 0522-4309858/59/60
Bhubaneswar : Tel: 0674-2546476	Ludhiana : Tel: 0161-5077028/29/30
Chandigarh : Tel: 0172-5089862/64	Mumbai : Tel: 022-30926666
Chennai : Tel: 044-40807676	Patna : Tel: 0612-2582282
Cochin : Tel: 0484-2808646	Pune : Tel: 020-25560300
Delhi NCR : Tel: 011-43834400/4500	Raipur : Tel: 0747-1115412
Ghaziabad : Tel: 0120-4205851	Ranchi : Tel: 0763-5093703
Indore : Tel: 0731-4005864	Secunderabad : Tel: 040-49134283
Jaipur : Tel: 0141-2218903/04/05/06	Vijaywada : Tel: 0866-2952224/25/26

To know more give a missed call or SMS:
<DAIKIN> to 9210188999
Visit us at: www.daikinindia.com
Follow us on:
f www.facebook.com/daikinindia
t www.twitter.com/daikinindia
in [company/daikin-airconditioning-india-pvt.-ltd.](https://www.linkedin.com/company/daikin-airconditioning-india-pvt.-ltd.)
@ <https://www.instagram.com/daikin.india/>

• The specifications, designs and information in this brochure are subject to change without notice.

As a continuing policy of product innovation at Daikin, the design and specifications are subject to change without prior notice. The visuals of the products in the catalogue are representative only, actual products might differ from the ones shown. Sales revenue includes revenue through sales of all Daikin Airconditioning Systems.

Product mentioned in this catalogue comply with RoHS regulations as per E-waste (Management & Handling) Rules, 2011 and should not be mixed with general household waste at the end of their useful life. For more details kindly visit our website www.daikinindia.com or contact our customer care centre at 011 - 4031 9300 / 1860 180 3900.



WORLD'S LEADING AIR CONDITIONING COMPANY FROM JAPAN



2in1
CONVERTIBLE
Freezer/Cooler

**INNOVATION THAT PRESERVES
FRESHNESS AND
RENEWS YOUR TRUST**



Gross Volume: - 341 litre
 Gross Dimensions: - 1188x703x960 mm
 Gross Weight: - 57 kg
 No. of Basket: - 1



Gross Volume: - 446 litre
 Gross Dimensions: - 1470x703x960 mm
 Gross Weight: - 65 kg
 No. of Basket: - 2



Gross Volume: - 556 litre
 Gross Dimensions: - 1760x703x960 mm
 Gross Weight: - 76 kg
 No. of Basket: - 2



MEGA FREEZER

Mega cooling, Mega capacity, approx 15% higher storage capacity.



D+ COOLING PIPES

More surface contact and large heat exchange area.



4D COOLING

Four side faster cooling. Uniform Temperature.



POWERFUL & FAST FREEZING

Preserve nutrition and flavours of foods better.

Specifications

Point		Unit	Model 1	Model 2	Model 3
Daikin Model No.			CRCF35DDARV16	CRCF45DDARV16	CRCF55DDARV16
Rated Voltage & Frequency			230V ± 20V & 50Hz	230V ± 20V & 50Hz	230V ± 20V & 50Hz
Capacity	Gross capacity	Ltr	341	446	556
	Net capacity	Ltr	315	413	514
Refrigerant Type		Type	R-134a	R-134a	R-134a
Refrigerant QTY		R134a Qty (gms)	110	120	155
Working functions		Convertible (Freezer to Cooler)/ Only freezer	Optional	Optional	Optional
Rated Power (+/- 7%)		Watts	212	218	250
Rated Input Current (+/- 7%)		Amps	1.72	1.95	2.1
Compressor	Compressor Type	Recip	Yes	Yes	Yes
	MODEL		MA88LHEP	MA88LHEP	GH12FAB
	Cooling Capacity	Watts	280 ± 7%	280 ± 7%	330 ± 7%
Fan motor	Type		Single phase Shaded pole Motor	Single phase Shaded pole Motor	Single phase Shaded pole Motor
	Wattage (Output)	W	5	5	10
	Impeller	mm	200	200	200
Condenser	Type	Wire On Tube	Yes	Yes	Yes
Foamed Cabinet	PUF Thickness	mm	60	60	60
	Outer/Inner Material	PPGI	PPGI (Pre-painted Galv. Steel)	PPGI (Pre-painted Galv. Steel)	PPGI (Pre-painted Galv. Steel)
	No of Basket	QTY -1/2	1	2	2
	No of lids	1/2	2	2	2
Dimensions	Gross(Packed) dimension(W*D*H)	mm	1188*703*960	1470*703*960	1760*703*960
	Net Unit dimension (W*D*H)	mm	1120*666*930	1402*666*930	1692*666*930
	Gross weight	Kg +/- 1kg	57	65	76
	Net weight	Kg +/- 1kg	51	58	66
Operation temperature range		°C	-20 to +6	-20 to +6	-20 to +6
Accessories with Unit	User & Installation Manual	Y/N	Y	Y	Y
	Keys	Y/N	Y(2)	Y(2)	Y(2)
	ICE SCRAPER	Y/N	N	N	N
Door with Gasket and Deep Door	PUF Thickness	mm	50	50	50
E-waste label			Y	Y	Y