

RELIABLE STORAGE. EXCEPTIONAL CONTROL.



Medical Refrigeration Products






For more information, please contact **BLUE STAR LIMITED** • **Ahmedabad:** 301 & 302, (3rd Floor), Abhishree Avenue, (Near) Nehru Circle, SM Road, Ambawadi, Ahmedabad - 380 015. Tel: (079) 40224000 • **Bengaluru:** Anjuman KAY A R R Tower No - 28, Ward No 77, Mission Road, Bangalore - 560027. Tel: (080) 41854000 • **Bhubaneshwar:** 3A, Satya Nagar, 2nd Floor, Bhubaneshwar - 751 007. Tel: (0674) 2572403 / 2573670 • **Chandigarh:** Adarsh Mall, 4th Floor, Plot No. 50, Industrial & Business Park, Phase - II, Chandigarh - 160 002. Tel: (0172) 5024000 • **Chennai:** KRM Plaza, No 2, Harrington Road, Chetpet, Chennai - 600 031. Tel: (91) (44) 42444000 • **Ghaziabad:** C 53A, Third Floor, Rajnagar District Center (RDC), Raj Nagar, Ghaziabad - 201001, Uttar Pradesh. Tel No: (0120) 2821400 • **Goa:** 210, 2nd Floor, Gera's Imperium I, Patto, Panjim, Goa - 403 001. Tel: (0832) 2438171/2437287 • **Gurgaon:** Block 2-A, DLF Corporate Park, DLF Qutab Enclave, Phase III, Mehrauli-Gurgaon Road, Gurgaon - 122 002. Tel: (0124) 4094100 • **Guwahati:** Oasis Plaza, Dr. B. Baroah Road, Ulubari, Kamrup, Guwahati - 781007. Tel: (0361) 2468496 • **Indore:** Shri Krishna Classic, First Floor, 139, Phadnis Colony, AB Road, Indore - 542 010. Tel: (0731) 4001211/4001311 • **Jaipur:** A-19, 1st Floor, Main Sahakar Path, Near Sahakar Bhavan, Jaipur - 302 001. Tel: (0141) 2744033-35 • **Kochi:** 2nd Floor, Millennium Plaza, MKK Nair Road, Alinchuvadu Junction, Kochi - 682 024. Tel: (0484) 4499000 • **Kolkata:** 7, Hare Street, Kolkata - 700 001. Tel: (033) 22134100 • **Ludhiana:** SCO 16-17, Feroze Gandhi Market, Fortune Chambers, 3rd Floor, Ludhiana - 141001 (Punjab), Tel: 0161 5001404 • **Lucknow:** 177/4, Faizabad Road, Lucknow - 226 007. Tel: (0522) 4034000 • **Mumbai:** Blue Star House, 9-A, Ghatkopar Link Road, Saki Naka, Mumbai - 400 072. Tel: (022) 66684100 • **Nagpur:** 219, Bajaj Nagar, 1st Floor, South Ambazari Road, Nagpur - 440 010. Tel: (0712) 2249000 / 6624000 • **Pune:** 201/A, Nityanand Complex, 1st Floor, 247/A, Bund Garden Road, Pune - 411 001. Tel: (020) 41044000 / 26169332 • **Raipur:** Alaska Corporates, 3rd Floor, Opp. VIP Road, Jivan Vihar Colony, G E Road, Raipur, Chhattisgarh - 492 006. Tel: (0771) 6544000 • **Secunderabad:** 207, Sikh Road, Bantia Estate, Secunderabad - 500 003. Tel: (040) 44004100 • **Thiruvananthapuram:** TC IV/962, 'Chandrika', Sree Chitra Nagar, PipeLine Road, Kawdiar, Thiruvananthapuram - 695 003. Tel: (0471) 2720025 / 65 • **Vadodara:** Ramakrishna Chambers, 7th Floor, Productivity Road, Alkapuri, Vadodara - 390 007. Tel: (0265) 2330334 / 6614100 • **Visakhapatnam:** D. No. 49-24-65/1, Near Sankarmatam Road, Madhura Nagar, Visakhapatnam - 530 016. Tel: (0891) 2748405/ 2748433 • **Vijayawada:** No. 40-1-62, Nagas Hafeez Plaza, Opposite to grand modern supermarket, Near BENZ Circle, MG. Road, Vijayawada 10. Tel No. : 0866 2484004. • **email:** coolingsolutions@bluestarindia.com • **Visit us at:** www.bluestarindia.com or SMS 'COOL' to 57575

Blue Star, India's leading Air conditioning and Refrigeration Company now brings to you freezer and refrigerators in various series of low and ultra low temperatures for scientific and medical purposes.

4°C Blood Bank Refrigerators

A blood bank refrigerator is a specialized refrigerating equipment for blood storage application. It's also used for cold storage of pharmaceuticals, biological products, vaccines, etc; typical for hospitals, epidemic prevention station, blood bank and other medical industries.

Features

-  Six advanced temperature sensors
-  Microprocessor controller for precision temperature
-  Security Control alarm Systems for various mal functions
-  Three different alarming methods: Buzzer, light flash & remote alarm
-  Power on delay, time between stops ; for more protection
-  Temperature recorders & printers
-  Safety door lock
-   Microprocessor Controller
-  Inner and outer double door design for effective insulation
-  LED lighting inside for content visibility
-  Multi-layer movable shelves
-  Universal castors with locking facility

Technical Specification

Description	Units	XC-310	XC-358	XC-400	XC-588
Capacity	Ltr.	310	358	400	588
Inner Temperature	°C	4±1	4±1	4±1	4±1
Voltage	V/Hz	220/50	220/50	220/50	220/50
Power	W	403	600	430	700
Interior Dimension (W X D X H)	mm	565 X 454 X 1198	512 X 515 X 1270	640 X 577 X 1195	515 X 560 X 1260
Exterior Dimension (W X D X H)	mm	660 X 644 X 1960	700 X 628 X 1962	750 X 761 X 1799	800 X 760 X 1977
Shelf/ Basket	Nos.	5/15	5	5/20	6
Net Weight / Gross Weight	kg	127/155	200/210	156/192	230/240

Medical Refrigerators

Blue Star's range of medical refrigerators comes with international compressor and rust free ABS plastic for more hygienic use. These are specialized refrigerating units for cold storage of pharmaceuticals as well as biological products. It is suitable for hospitals, drugstores, pharmaceutical factories, sanitation and anti epidemic station and clinics.

2°C to 8°C Pharmacy Refrigerators

Features

-  Microprocessor controller for precision temperature
-  Security Control alarm Systems for various mal functions
-  Three different alarming methods: Buzzer, light flash & remote alarm
-  Power on delay, time between stops ; for more protection
-  Rust free ABS plastic for more hygienic use.
-  LED lighting and glass door for clear content visibility
-   Microprocessor Controller
-  Safety door lock
-  Multi-layer movable shelves

Technical Specification

Description	Units	YC-280	YC-370
Capacity	Ltr.	280	370
Inner Temperature	°C	2°C to 8°C	2°C to 8°C
Voltage	V/Hz	220/50	220/50
Power	W	265	265
Interior Dimension (W X D X H)	mm	504 X 460 X 1150	570 X 475 X 1370
Exterior Dimension (W X D X H)	mm	595 X 565 X 1661	661 X 565 X 1881
Shelf/ Basket	Nos.	3/1	4/1
Net Weight / Gross Weight	kg	75/85	80/90

2° C to 10°C Medical Refrigerators (stainless steel finish)

These are specialized refrigerating unit which are rugged and comes with a unique auto defrost system.

Features

-  Microprocessor controller for precision temperature
-  Combination of two sensors and auto defrost mechanism.
-  Audible and Visual alarm systems
-  Safety door lock
-  Stainless steel exterior and interior
-  LED lighting and glass door for clear content visibility
-  Double glass door with heater to prevent ice leaks
-  Multi-layer movable shelves with blood storage basket
-  Data logging with printer: Chart recorder is optional
-  Ecofriendly refrigerant with R134a (CFC free)



Technical Specification

Description	Units	YC-330	YC-520	YC-965	YC-1500
Capacity	Ltr.	330	520	965	1500
Inner Temperature	°C	+2 to +10	+2 to +10	+2 to +10	+2 to +10
Voltage	V/Hz	220/50	220/50	220/50	220/50
Power	W	220	350	750	900
Interior Dimension (W X D X H)	mm	475 X 540 X 1335	590 X 670 X 1450	600 X 1100 X 1400	1415 X 635 X 1680
Exterior Dimension (W X D X H)	mm	570 X 642 X 1940	710 X 785 X 1975	750 X 1200 X 1965	748 X 1800 X 1965
Shelf/ Basket	Nos.	4	4	8	12
Net Weight / Gross Weight	kg	100/110	120/130	170/180	230/250

Medical Freezers

Blue Star range of ultra-low upright freezers comes with highly efficient compressors and eco-friendly refrigerants. These medical freezers offers a wide variety of research and storage applications such as low temperature scientific experiments, preservation of plasma, biomaterials, vaccines and biomedical properties of military products. It is suitable for research institutes, electronic industries, chemical engineering industries, hospitals, university laboratories, military industries, sanitation and anti-epidemic stations.

-25°C Upright Medical Freezer

Features

-  Microprocessor controller for precision temperature
-  Audible and Visual alarm systems
-  ABS plastic for inner cabinet and painted steel for external body
-  Safety door lock
-  Heavy duty castors
-  Drawers for easy storage
-  Chart Recorder (Optional)
-  Ecofriendly Refrigerant with R507(CFC free)









Technical Specification



Description	Units	DW-25L276	DW-YL450
Capacity	ltr.	276	450
Inner Temperature	°C	-25°C	-25°C
Voltage	V/Hz	220/50	220/50
Power	W	272	450
Interior Dimension (W X D X H)	mm	506 X 505 X 1205	530 X 626 X 1356
Exterior Dimension (W X D X H)	mm	717 X 710 X 1745	655 X 780 X 1845
Net Weight / Gross Weight	Kg	106/125	120/140

-40°C Upright Medical Freezer

Features

-  Microprocessor controller for precision temperature
-  Audible and visual alarm systems with password protection configuration page.
-  ABS plastic for inner cabinet and painted steel for external body
-  Safety door lock
-  Heavy duty castors
-  Drawers for easy storage




-  Chart Recorder (Optional)
-  Ecofriendly Refrigerant with R507(CFC free)

Technical Specification

Description	Units	DW-FL90	DW-FL270
Capacity	Ltr.	90	270
Inner Temperature	°C	-40	-40
Voltage	V/Hz	220/50	220/50
Power	W	280	370
Interior Dimension (W X D X H)	mm	438 X 388 X 539	438 X 388 X 1680
Exterior Dimension (W X D X H)	mm	623 X 544 X 842	623 X 544 X 1680
Net Weight / Gross Weight	kg	44/48	65/70

-86°C Upright Medical Freezer

Features

-  Microprocessor controller for precision temperature
-  Audible and visual alarm systems
-  Stainless steel interior and pre-painted steel exterior body
-  Lockable door with full height handle, with vacuum release port.
-  Adjustable Stainless steel shelves with inner door, double silicon gasket seal.
-  Heavy duty castors
-  Optional : Chart recorder, CO2 backup system, storage racks/boxes, remote alarm systems
-  Two-times foaming technology. 155mm foaming insulation, with VIP+.
-  Patented technology of CFC free mixture refrigerant (R134a, R404a, R23,R410A, N2 etc.)
-  Keyboard lock & password protected configuration page; delayed start & safe stop interval between restart & being terminated
-  With temperature printer, record 7days data. 72 hours battery back up for printer and controller display.



Technical Specification

Description	Units	DW-HL218	DW-HL388S	DW-HL538S
Capacity	Ltr.	218	388	538
Inner Temperature	°C	-10°C to -86°C	-10°C to -86°C	-10°C to -86°C
Voltage	V/Hz	220/50	220/50	220/50
Power	W	1000	1800	2000
Interior Dimension (W X D X H)	mm	582 X 470 X 768	740 X 450 X 1200	662 X 600 X 1330
Exterior Dimension (W X D X H)	mm	940 X 840 X 1552	940 X 840 X 1999	940 X 840 X 1999
Net Weight / Gross Weight	kg	225/250	330/360	360/380